

TX HMI/PLC Series
Plug-In Module
RS232 Interface
TX-RS232






- Plug-in expansion module for use with HMIs of the TX500 and TX700 product series
- RS232 Interface
- 9-pin SUB-D female connector
- With plug-in expansion slot

Type designation	TX-RS232
Ident no.	100002599
Supply	
System power supply	From the HMI
System data	
Fieldbus connection technology	1 × 9-pol D-SUB, Female connector
Electrical isolation	no
Approvals and certificates	
	CE, cULus
General Information	
Dimensions (W x L x H)	41.2 x 90.3 x 23.8mm
Operating temperature	-20...+60 °C
Storage temperature	-20...+70 °C
Relative humidity	5...85 %, non-condensing
Protection class	IP20
Housing material	Metal
Housing color	Silver
Mounting	On HMIs of the TX500 and TX700 series

TX HMI/PLC Series
Plug-In Module
RS232 Interface
TX-RS232

Connection and pin assignment

	<p>Serial Interface SUB-D female connector, 9-pin</p>	<p>Pin Assignment RS232</p>  <ul style="list-style-type: none"> 1 = GND 2 = n.c. 3 = TX 4 = RX 5 = n.c. 6 = +5V output 7 = CTS 8 = RTS 9 = n.c.
	<p>Port for Plug-in Module The expansion slot can be used for another plug-in module. The possible module combinations are described in the manual for the base units.</p>	