YI2A14-020VB3XLEAX



YI2A14-020VB3XLEAX



Ordering information

| Туре | Part no. |
|--------------------|----------|
| YI2A14-020VB3XLEAX | 2096222 |
| | |

Only suitable for PNP sensors

Other models and accessories -> www.sick.com/



Detailed technical data

Technical specifications


| Accessory group | Plug connectors and cables |
|-------------------------|---|
| Accessory family | Connecting cables |
| Connection type head A | Female connector, M12, 4-pin, angled, A-coded |
| Connection type head B | Flying leads |
| Locking plug connector | Screw connection |
| Connector material | TPU |
| Connector color | Transparent |
| Locking nut material | Zinc die-cast, nickel-plated |
| Seal material | FKM |
| Tightening torque | 0.6 Nm |
| Width across flats | 13 |
| Cable | 2 m, 4-wire, PVC |
| Jacket material | PVC |
| Jacket color | Gray |
| Cable diameter | 5 mm |
| Conductor cross-section | 0.34 mm ² |
| Shielding | Unshielded |
| Bending radius | |
| Flexible use | > 10 x cable diameter |
| Stationary position | > 5 x cable diameter |
| Display LED | ✓ |
| Reference voltage | ≤ 24 V DC |
| Rated impulse voltage | 0.8 kV |
| Current loading | 4 A |
| Signal type | Sensor/actuator cable |
| Application | Zones with chemicals |
| Note | Only suitable for PNP sensors |
| Authorizations | UL |

| UL File No. | E335179 |
|--------------------------------|--|
| Enclosure rating | IP65 / IP66K / IP67 |
| Description | LED function display |
| Specialty | LED function indicator |
| Ambient operating temperature | |
| Flexible use | -5 °C +80 °C |
| Stationary position | -30 °C +80 °C |
| Head | -25 °C +85 °C |
| Contamination rating | 3 |
| Insulation resistance | 100 ΜΩ |
| Overvoltage category | III |
| Specific insulation resistance | 30 mΩ |
| Thermal resistance, cable | Flame retardant according to UL 1581 VW1 / CSA FT1 |

Classifications

| ECI@ss 5.0 | 19030312 |
|----------------|----------|
| ECI@ss 5.1.4 | 19030312 |
| ECI@ss 6.0 | 27060304 |
| ECI@ss 6.2 | 27060304 |
| ECI@ss 7.0 | 27060304 |
| ECI@ss 8.0 | 27060304 |
| ECI@ss 8.1 | 27060304 |
| ECI@ss 9.0 | 27060304 |
| ECI@ss 10.0 | 27060304 |
| ECI@ss 11.0 | 27060304 |
| ETIM 5.0 | EC000830 |
| ETIM 6.0 | EC000830 |
| ETIM 7.0 | EC003249 |
| UNSPSC 16.0901 | 26121604 |

Dimensional drawing (Dimensions in mm (inch))



YI2A14-020VB3XLEAX

Recommended accessories

Other models and accessories → www.sick.com/

| | Brief description | Туре | Part no. | | |
|----------------------------|---|------------------|----------|--|--|
| Other mountir | ng accessories | | | | |
| | 1 piece, M12 mounting key set for SW13 with calibrated torque 0.6 Nm | TOOL-TW06M12AF13 | 5337208 | | |
| Plug connectors and cables | | | | | |
| | Head A: female connector, M12, 5-pin, straight Cable: unshielded | DOS-1205-G | 6009719 | | |
| | Head A: male connector, M12, 5-pin, straight Cable: unshielded For field bus technology | STE-1205-G | 6022083 | | |

SICK AT A GLANCE

SICK is one of the leading manufacturers of intelligent sensors and sensor solutions for industrial applications. A unique range of products and services creates the perfect basis for controlling processes securely and efficiently, protecting individuals from accidents and preventing damage to the environment.

We have extensive experience in a wide range of industries and understand their processes and requirements. With intelligent sensors, we can deliver exactly what our customers need. In application centers in Europe, Asia and North America, system solutions are tested and optimized in accordance with customer specifications. All this makes us a reliable supplier and development partner.

Comprehensive services complete our offering: SICK LifeTime Services provide support throughout the machine life cycle and ensure safety and productivity.

For us, that is "Sensor Intelligence."

WORLDWIDE PRESENCE:

Contacts and other locations -www.sick.com



Online data sheet

