

D E S C R I P T I O N

PRODUCT COVERED:

* Component - Terminal blocks, Types ZPE 2.5, ZPE 2.5/3AN, ZPE 2.5/4AN, ZPE 6. ZDU 2.5, ZDU 2.5/3AN, ZDU 2.5/2X2AN, ZDU 2.5/4AN, ZDU 4, ZPE 4, ZDU 6, ZTR 2.5, ZTR 2.5 D, ZTR 2.5/D/DRBR, ZTR 2.5/3AN, ZTR 2.5/3AN/D+ or /D-, ZTR 2.5/3AN/DRBR; ZSI 2.5 and ZSI 2.5/2 may be followed by /LED.

GENERAL:

These devices are multicircuit terminal blocks which provide spring connectors for conductor termination.

ELECTRICAL RATINGS:

| Type | Copper Conductors, Wire Range, AWG Solid/Stranded | | Current A | Maximum Volts, V ac For Devices Having | | Torque Lb In. |
|---|---|---------|--------------|--|-------|------------------|
| | Field | Factory | | Gen. Ind. | Comm. | |
| ZPE 2.5, ZPE 2.5/3AN, ZPE 2.5/4AN | 26-12 | 26-12 | N/A | N/A | - | N/A |
| ZPE 6 | 22-8 | 22-8 | N/A | N/A | - | N/A |
| ZDU 2.5, ZDU 2.5/3AN, ZDU 2.5/4AN, ZDU 2.5/2X2AN | 26-12 | 26-12 | 25 | 600 | 600 | N/A |
| ZDU 6 | 22-8 | 22-8 | 45 | 600 | 600 | N/A |
| ZTR 2.5 | 26-12 | 26-12 | 10 | 300 | 250 | N/A |
| ZTR 2.5 D | 26-12 | 26-12 | - | 300 | 250 | N/A |
| ZTR 2.5/D/DRBR | 26-12 | 26-12 | - | 300 | 250 | N/A |
| *ZTR 2.5/3AN, *ZTR 2.5/3AN/D, *ZTR 2.5/3AN/DRBR | 26-12 | 26-12 | 10 | 300 | 300 | N/A |
| ZSI 2.5, ZSI 2.5/LED | 26-12 | 26-12 | 10 | 300 | 250 | N/A |
| ZSI 2.5/2, ZSI 2.5/2/LED | 26-12 | 26-12 | 16 | 600 | 600 | N/A |
| ZDU 4 | 26-10 | 26-10 | 33 | 600 | 600 | N/A |
| ZPE 4 | 26-10 | 26-10 | 33 | N/A | - | N/A |
| | | | | | | |