

**Terminals****Part Number: 1706090000****ZPE 2.5-2/3AN****PE terminal**

Representative Photo

**Selected Features**

<b>Installation advice</b>	TS 35
<b>Type of connection</b>	Tension spring connection
<b>Insulation material</b>	Wemid
<b>Rated voltage</b>	800 V
<b>Rated cross-section</b>	2.5 mm <sup>2</sup>
<b>Version</b>	PE terminal
<b>Colour of insulating material</b>	green
<b>Rated impuls voltage</b>	8 kV

## Additional Technical Data

<b>EAN</b>	4008190915438
<b>Width</b>	5 mm
<b>Length</b>	50.5 mm
<b>No. of identical terminals</b>	1
<b>Plug gauge</b>	A2
<b>min. conductor</b>	0.13 mm <sup>2</sup>
<b>max. conductor</b>	2.5 mm <sup>2</sup>
<b>Height with TS</b>	43 mm
<b>Degree of soiling</b>	3
<b>min. rated cross-section (UL)</b>	26 AWG
<b>max. rated cross-section (UL)</b>	12 AWG
<b>min. rated cross-section (CSA)</b>	26 AWG
<b>max. rated cross-section (CSA)</b>	14 AWG
<b>Stripping length</b>	10 mm
<b>Solid, min.</b>	0.5 mm <sup>2</sup>
<b>Solid, max.</b>	2.5 mm <sup>2</sup>
<b>Flexible, min.</b>	0.5 mm <sup>2</sup>
<b>Flexible, max.</b>	2.5 mm <sup>2</sup>
<b>Flexible and ferrule, min. (DIN 46228-1)</b>	0.5 mm <sup>2</sup>
<b>Flexible and ferrule, max. (DIN 46228-1)</b>	1.5 mm <sup>2</sup>
<b>ferrule with plastic insul. collar, min.</b>	0.5 mm <sup>2</sup>
<b>ferrule with plastic insul. collar, max.</b>	1.5 mm <sup>2</sup>

**Product Liability** The above information describes our products. It does not constitute guaranteed properties and is not intended to affirm the suitability of a product for a particular application. Regrettably, omissions and exceptions cannot

be completely ruled out. Technical data are always specified by their average values. Exact data and the tolerances which apply to our processes can be requested from:

Weidmüller - North America  
United States 001 (800) 849-9343  
Canada 001 (800) 268-4080

or

Weidmüller - Germany  
Telephone operator 0049 (-5252) 960-0

