

Selection Aid for Compact Direct On Line Starters



RS Order Code	Manufacturer Order Code & Coil Operating Voltage	Current Adjustment Range	Suitable Three Phase Motor at 400V "Direct On Line"	Dimensions H x W x D (mm)
		(A)	(kW)	
812-9073	DOLC0.37 230	0.9-1.5	0.25-0.37	175 x 88 x 109
812-9077	DOLC0.37 400	0.9-1.5	0.25-0.37	175 x 88 x 109
812-9086	DOLC0.75 230	1.4-2.3	0.55-0.75	175 x 88 x 109
812-9089	DOLC0.75 400	1.4-2.3	0.55-0.75	175 x 88 x 109
812-9083	DOLC1.1 230	2.0-3.3	0.75-1.1	175 x 88 x 109
812-9092	DOLC1.1 400	2.0-3.3	0.75-1.1	175 x 88 x 109
812-9095	DOLC2.2 230	3-5	1.5-2.2	175 x 88 x 109
812-9099	DOLC2.2 400	3-5	1.5-2.2	175 x 88 x 109
812-9109	DOLC4.0 230	6-10	3-4	175 x 88 x 109
812-9102	DOLC4.0 400	6-10	3-4	175 x 88 x 109

General Characteristics
Insulated polycarbonate enclosure
Operating temperature: -25...+60°C
Storage temperature: -40...+70°C
Degree of protection: IP65
Compliant with standards: IEC/EN 60947-1 and IEC/EN60947-4-1

Indicated powers apply to 4-Pole motors; it is advisable to always check the nameplate motor current is within the relay adjustment range.

