

1) Mode settings, 2) Emitter, 3) Optical axis, 4) Receiver, 5) Power indicator, 6) stability, 7) Sensitivity, 8) Sensitivity



### Basic features

Approval/Conformity	cULus CE UKCA EAC WEEE
Principle of operation	Photoelectric sensor
Series	R090K
Style	Square Connection 45°

### Display/Operation

Adjuster	Potentiometer 270° Rotary switch 2 positions
Display	Output function- LED yellow Stability - LED green
Setting	Sensitivity (Sn) Light-on/dark-on

### Electrical connection

Cable diameter D	3.50 mm
Cable length L	2 m
Conductor cross-section	0.20 mm <sup>2</sup>
Connection	Cable, 2.00 m, PVC
Polarity reversal protected	yes
Short-circuit protection	yes

### Electrical data

No-load current I <sub>o</sub> max. at U <sub>e</sub>	20 mA
Operating voltage U <sub>b</sub>	10...30 VDC
Rated operating current I <sub>e</sub>	100 mA
Rated operating voltage U <sub>e</sub> DC	24 V
Ready delay t <sub>v</sub> max.	300 ms
Ripple max. (% of U <sub>e</sub> )	10 %
Switching frequency	1000 Hz
Turn-off delay t <sub>off</sub> max.	0.5 ms
Turn-on delay t <sub>on</sub> max.	0.5 ms
Voltage drop U <sub>d</sub> max. at I <sub>e</sub>	2 V

Photoelectric Sensors  
**BOS R090K-PU-RX10-02**  
**Order Code: BOS02AW**

**BALLUFF**

**Environmental conditions**

Ambient temperature	-30...55 °C
IP rating	IP67

**Functional safety**

MTTF (40 °C)	94 a
--------------	------

**Interface**

Switching output	PNP normally open/normally closed (NO/NC)
------------------	---

**Material**

Housing material	PC PBT
Material jacket	PVC
Material sensing surface	PMMA

**Mechanical data**

Dimension	10.7 x 32.7 x 19.5 mm
Mounting part	Screw M3
Tightening torque max.	0.5 Nm


**Optical features**

Ambient light max.	10000 Lux
Beam characteristic	Divergent
Light type	LED, red light
Principle of optical operation	Through-beam sensor
Switching function, optical	dark-on/light-on
Wave length	660 nm

**Range/Distance**

Range	0...20 m
Rated operating distance Sn	20 m

**Wiring Diagrams**



**Opto Symbols**

