

Electromechanical impulse counters

→ Impulse counters - CIM 36 x 48

- 5 or 6 digits, height of digits 4 mm
- With or without manual reset
- White digits on a black background



Part numbers


Type	Number of digits	Operating frequency (Hz)	Voltages	Code
Without manual reset	6	50 / 60	230 V~	99776701
	6	50 / 60	115 V~	99776702
	6	50 / 60	24 V~	99776704
	6	V=	110 V=	99776705
	6	V=	24 V=	99776707
	6	V=	48 V=	99776736
With manual reset	5	50 / 60	230 V~	99776710
	5	50 / 60	115 V~	99776711
	5	50 / 60	24 V~	99776713
	5	V=	24 V=	99776716

General characteristics


General characteristics	
Counting capacity	999.999 impulses without manual reset 99.999 impulses with manual reset
Height digits (mm)	4
Max. count rate	V~ → 18 impulses/s V= → 25 impulses/s
Min. count rate	V~ → 28 ms V= → 20 ms
Min pause time between 2 pulses	V~ → 28 ms V= → 20 ms
Max. pulse length (count coil)	Unlimited
Voltage variation	+ 10% / -15% Un
Consumption	24 V~ / 115 V~ : 1.1 VA 230 V~ : 2.1 VA 110 V= : 1 W 48 V= : 0.8 W 24 V= : 0.8 W
Mechanical life count function (operations)	> 50 x 10 ⁶
Test voltage according to standard IEC 255-5	U < 60 V: 500 V U > 60 V: 2 000 V
Protection Housing	IP40
Degree of terminal protection	IP00
Environmental protection	Plated or stainless steel components
Maintenance	None
Operating position	Any
Temperature limits use (°C)	-10 → +60
Temperature limits stored (°C)	-40 → +80
Certifications	CE
Connection	6.35 Faston connectors or screw terminals
Mounting	2 x 2.5 Ø screws - F90° on front face
Weight (g)	50

Dimensions (mm)


9977670/3 - Rear faces




Panel cut-out



9977671 - Rear faces



9977670/3 - 6 digits



9977671 - 5 digits

