

Terminals**Part Number: 1706100000****ZPE 2.5-2/4AN****PE terminal**

Representative Photo

Selected Features

Installation advice	TS 35
Type of connection	Tension spring connection
Insulation material	Wemid
Rated voltage	800 V
Rated cross-section	2.5 mm ²
Version	PE terminal
Colour of insulating material	green
Rated impuls voltage	8 kV

Additional Technical Data

EAN	4008190915445
Width	5 mm
Length	50.5 mm
No. of identical terminals	1
Plug gauge	A2
min. conductor	0.13 mm ²
max. conductor	2.5 mm ²
Height with TS	43 mm
Degree of soiling	3
min. rated cross-section (UL)	26 AWG
max. rated cross-section (UL)	12 AWG
min. rated cross-section (CSA)	26 AWG
max. rated cross-section (CSA)	14 AWG
Stripping length	10 mm
Solid, min.	0.5 mm ²
Solid, max.	2.5 mm ²
Flexible, min.	0.5 mm ²
Flexible, max.	2.5 mm ²
Flexible and ferrule, min. (DIN 46228-1)	0.5 mm ²
Flexible and ferrule, max. (DIN 46228-1)	1.5 mm ²
ferrule with plastic insul. collar, min.	0.5 mm ²
ferrule with plastic insul. collar, max.	1.5 mm ²

Product Liability The above information describes our products. It does not constitute guaranteed properties and is not intended to affirm the suitability of a product for a particular application. Regrettably, omissions and exceptions cannot

be completely ruled out. Technical data are always specified by their average values. Exact data and the tolerances which apply to our processes can be requested from:

Weidmüller - North America
United States 001 (800) 849-9343
Canada 001 (800) 268-4080

or

Weidmüller - Germany
Telephone operator 0049 (-5252) 960-0

