

# Fluid System Shut-Off Valves Inch Polypropylene

The PPSV Range of inch-size shut-off valves is offered for tube sizes 1/4" OD and 3/8" OD. These valves are produced in white polypropylene and fitted with EPDM O-rings. Polypropylene has the advantage of being more chemically resistant than acetal. These valves are for use with potable water.

## Working pressures and temperatures

Water Max. 150 psi at 70 °F (Max. 10 bar at 20 °C)

Max. 60 psi at 140 °F (Max. 4 bar at 60 °C)

Min. 33 °F/1 °C

**NOT suitable for compressed air, explosive gases, petroleum spirits and other fuels, or for heating systems**

For general technical specifications, refer to page 76.



NSF 51  
NSF 61

### Shut-Off Valve (Male) Speedfit to Male (NPTF Thread)



Part Number	Tube OD	Thread NPTF	Bag Qty	Box Qty
PPSV010822W-US	1/4"	1/4"	200	200
PPSV011223W-US	3/8"	3/8"	100	100

### Straight Shut-Off Valve Speedfit to Speedfit



Part Number	Tube OD	Bag Qty	Box Qty
PPSV040808W-US	1/4"	200	200
PPSV041212W-US	3/8"	80	80

Also available in black. Use suffix E.

### Shut-Off Valve (Female) Speedfit to Female (NPTF Thread)



Part Number	Tube OD	Thread NPTF	Bag Qty	Box Qty
PPSV451223W	3/8"	3/8"	80	80

Also available in black. Use suffix E.

### Shut-Off Valve (Female Elbow) Speedfit to Female (NPTF Thread)



Part Number	Tube OD	Thread NPTF	Bag Qty	Box Qty
PPSV500822W-US	1/4"	1/4"	200	200
PPSV501222W-US	3/8"	1/4"	100	100

● 1/4 Turn Valve indicated by this marker